

# Filling

## Automatic Auger Type Powder Filling Machine

MODEL SBAF -60/80/100/120

### Salient Features:

- ▶ Total Compact GMP model.
- ▶ "NO BOTTLE, NO FILL" System eliminates wastage of costly powder.
- ▶ Conveyor driving is through High quality imported Gear motor
- ▶ Machine speed can be adjusted by A.C. Frequency drive, which is time saving.
- ▶ Machine is provided with delrin conveyor belt to avoid sticking of Bottle on conveyor.
- ▶ Imported Gear Motor for Conveyor drive.
- ▶ A.C. Frequency drives for Conveyor drive.



### Technical Specification :

Model	SBAF-60	SBAF-80	SBAF-100	SBAF-120
Direction	Left To Right.	Left To Right.	Left To Right.	Left To Right.
Output	15-20 BPM - Depend on fill size	20-50 BPM -Depend on fill size	50-80 BPM - Depend on fill size	80-120 BPM - Depend on fill size
Fill Capacity	10gm-1 Kg with help of change parts	10gm-1 Kg with help of change parts	10gm-1 Kg with help of change parts	10gm-1 Kg with help of change parts
Powder Accuracy	± 1%	± 1%	± 1%	± 1%
No. of Heads	Single	Double	Three	Four
Electrical Supply	1.00 HP For Main Drive. 0.25 HP for conveyor	2.00 HP For Main Drive. 0.25 HP for conveyor	3.00 HP For Main Drive. 0.25 HP for conveyor	3.00 HP For Main Drive. 0.25 HP for conveyor
Power Requirement	230 Volts, 50 Hz.	230 Volts, 50 Hz.	230 Volts, 50 Hz.	230 Volts, 50 Hz.
Height of Conveyor	Adjustable from 800 To 850 MM	Adjustable from 800 To 850 MM	Adjustable from 800 To 850 MM	Adjustable from 800 To 850 MM

